

TECHNICAL DATASHEET

BMA POWDER PUTTY

Code: DIF-PUT060

Color: White-Gray

PROPERTIES

Powder Putty is a powder that contains cement, a specially formulated filler, and chemical additives to enhance its properties. It is a smoothing chemical for interior and exterior plastering.

RECOMMENDED USES

BMA Powder Putty can be used for:

- ✓ Filling small holes and fissures
- ✓ Exterior and interior application
- √ Smoothing plasters on walls and ceilings

PERFORMANCE BENEFITS

- ✓ Resistant to weathering conditions
- ✓ Good adhesion to concrete, cement and lime plaster surfaces
- ✓ Ready to use after adding water

CHARACTERISTIC PHYSICO-CHEMICAL DATA

Data corresponding to Powder Putty, DIF-PUT060

Tests	Norms	Results
Density (kg/lt.) @ 25°C	ASTM D1475	0.98 ± 0.05
Consumption Rate	-	350-400 gm/m²/coat thickness 200-225 μ

Fax: +961 1 885685

E-mail: customerservice@bmapaints.com



TECHNICAL DATASHEET

Application

The surface should be clean, and free of all contaminants, dust, oils, grease before applying the BMA Powder Putty. Add water to Powder Putty in the following proportions: 40 - 45 L water: 100 kg powder, thoroughly mixed. Therefore, depending on the roughness of the surface, apply one or more coats of Powder Putty with a putty knife. Before applying the next coat, each layer should be dried and sanded down. Water should be used to clean tools immediately after use.

Drying Time

Drying time = 4 hours

AVAILABLE PACKAGING

Bag: 25 kg

SHELF LIFE

BMA Powder Putty should be kept in tightly closed, undamaged containers that are not too humid. Exposure to direct sunlight should be avoided. BMA powder putty is stored 12 months under proper and dry storing conditions.

Under the above mentioned conditions, the shelf life BMA Powder Putty will be 2 years.

After this period, the paint quality is subjected to re-inspection. Proper handling is required to maintain good quality.

HEALTH & SAFETY

Before using this product please consult our Safety Data Sheet (SDS) for complete information on Hazards Identification, First-Aid and Fire-Fighting Measures, Accidental Release Measures, Handling and Storage, Exposure Control and Personal Protection, Stability and Reactivity, Toxicological Information, and Transport Information.

QUALITY ASSURANCE

BMA Commercial & Industrial s.a.l is a holder of the ISO 9001:2015 and ISO 45001:2018 certificates, which guarantees that all operations are conducted in compliance with International Standards.

2 | 3

Nahr El Mot, Industrial Valley - Lebanon Tel.: +961 1 885385/485

Fax: +961 1 885685

E-mail: customerservice@bmapaints.com



TECHNICAL DATASHEET

TDS.225 - Edition #: 1

IMPORTANT: The statements, technical information and recommendations contained herein are believed to be accurate. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, BMA Commercial & Industrial s.a.l expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

Fax: +961 1 885685